

MATERIAL SAFETY DATA SHEET

MANUFACTURED FOR:

PREPARATION DATE 10/1/2010

Manufactured By:
CLEARCO PRODUCTS CO., INC
3430-G PROGRESS DRIVE
Bensalem, PA 19020

Emergency Telephone Number
CHEM-TEL: 1 (800) 255-3924
CHEM TEL: 1-800-255-3924 (DOMESTIC)
+01-813-248-0585 (INTERNATIONAL)

Date Prepared: 10/1/2010

SECTION 1 - GENERAL INFORMATION - CLEARCO MIST ADHESIVE SPRAY 600

SECTION 2 – COMPOSITION/INFORMATION ON INGREDIENTS

EXPOSURE LIMITS

CHEMICAL NAME	CAS Number	Wt/Wt% LESS THAN	ACGIH		OSHA		COMPANY TLV-TWA	SKIN
			TLV-TWA	TLV-STEL	PEL- TWA	PEL- CEILING		
Hexane	110-54-3	35.0%	50 ppm.	N.E.	500 ppm	N.E.	N.E.	NO
Acetone	67-64-1	20.0%	500 ppm	750 ppm	1000 ppm	N.E.	N.E.	NO
Isobutane	75-28-5	15.0%	N.E.	N.E.	N.E.	N.E.	1000 ppm	NO
Propane	74-98-6	10.0%	2500 ppm	N.E.	1000 ppm	N.E.	N.E.	NO
Dimethyl Ether	115-10-6	10.0%	N.E.	N.E.	N.E.	N.E.	1000 ppm	NO

(See Section 16 for abbreviation legend)

SECTION 3 – HAZARDS IDENTIFICATION

*** **EMERGENCY OVERVIEW***** Keep from reach of children. Do not puncture, incinerate, or place aerosol product containers in compactors. Containers of this material may be hazardous when emptied since containers retain product residues (vapor, liquid, and/or solid). All hazard precautions given must be observed. Do not flame cut, braze or use welding torch. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.

EFFECTS OF OVEREXPOSURE – EYE CONTACT: Can cause severe irritation, redness, tearing, blurred vision.

EFFECTS OF OVEREXPOSURE – SKIN CONTACT: Prolonged or repeated contact can cause moderate irritation defatting, dermatitis.

EFFECTS OF OVEREXPOSURE – INHALATION: Excessive inhalation of vapors can cause nasal and respiratory irritation, dizziness, weakness, fatigue, nausea, headache, possible unconsciousness, and even asphyxiation. Overexposure may cause damage to the nervous system.

EFFECTS OF OVEREXPOSURE – INGESTION: No Information.

EFFECTS OF OVEREXPOSURE – CHRONIC HAZARDS: Overexposure to this material (or its components) has apparently been found to cause the following effects in laboratory animals: kidney damage, eye damage, liver damage, lung damage, nasal damage, nervous system damage, testis damage, Overexposure to this material (or its components) has apparently been found to cause the following effects in humans: visual impairment, central nervous system effects.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT, SKIN ABSORPTION, INHALATION , EYE CONTACT

SECTION 4 – FIRST AID MEASURES

FIRST AID: EYE CONTACT: Flush with large amounts of water, lifting upper and lower lids occasionally, get medical attention.

FIRST AID: SKIN CONTACT: Thoroughly wash exposed area with soap and water. Remove contaminated clothing. Launder contaminated clothing before re-use. Get medical attention if irritation persists. Mineral oil, baby oil, makeup remover, mineral spirits, or other similar mild solvent may be used to remove the sticky resin residue left by the adhesive.

FIRST AID: INHALATION: Remove individual to fresh air. If breathing is difficult, administer oxygen. Give artificial respiration if breathing has stopped. Keep person warm and quiet. Get medical attention.

FIRST AID: INGESTION: Do not induce vomiting. Give two glasses of water if conscious. Never give anything by mouth to an unconscious person. Get immediate medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point -156° F
(Pensky-Martens Closed Cup) Lower Explosive Limit: 1.0%
Upper Explosive Limit: 18.0%

AUTOIGNITION TEMPERATURE: N.D.

Extinguishing Media.....CO2, Dry Chemical, Foam, Water Fog

Unusual Fire & Explosion Hazards.....Vapors are heavier than air and travel along the ground or may be moved by ventilation and ignited by ignition sources at locations distant from material handling point. For aerosol products - exposure to temperatures over 130°F may cause containers to burst, releasing highly flammable gas.

Special Fire-fighting Procedures.....Wear self-contained breathing apparatus with a full face-piece operated in pressure-demand or other positive pressure mode when fighting fires. Keep fire exposed containers cool with water fog.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Steps to be taken in case Material is Released or Spilled: Eliminate sources of ignition & ventilated area. Persons not properly equipped should be excluded from area. Stop spill at source - prevent spreading. Avoid Inhalation of vapors. Avoid skin contact with liquid. Soak up on absorbent material and place into container for disposal. Use non-spark scoops for flammable materials. Clean walking surfaces thoroughly to reduce slipping hazard.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Containers of this material may be hazardous when emptied, since containers retain product residues (vapor, liquid, and/or solid). All hazard precautions given must be observed. Do not flame cut, braze or use welding torch on containers. Intentional misuse by deliberately concentrating and inhaling the vapors from this product may be harmful or fatal.

STORAGE: Do not store above 120°F. Do not store in direct sunlight. Keep away from heat sources, open flame, pilot lights, sparks, and other sources of ignition.

SECTION 8 - EXPOSURE CONTROLS/ PERSONAL PROTECTION

Engineering Controls: Provide sufficient mechanical ventilation (general and/or local exhaust) ventilation to maintain exposure below TLV(s).

Respirator Protection If workplace exposure limits of product or any component is exceeded, use a NIOSH/MSHA respirator. Consult your safety equipment supplier for recommendations.

Skin Protection: Wear impervious gloves if method of use involves skin contact with product. Consult your safety supply vendor for glove recommendations.

Eye Protection Wear safety glasses at minimum, more extensive protection may be necessary depending on how the product is to be used.

Other Protective Equipment: Wear impervious clothing if bodily exposure is anticipated. Consult your safety supply vendor for recommendations.

Hygienic Practices Wash hands before eating or smoking. Smoke in designated areas only. Remove and launder clothing if contaminated.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point (F).....	-44- 500°F	Vapor Density:	Heavier than air
Odor.....	Mint when wet	Odor Threshold:	N.D.
Appearance	White Liquid	Evaporation Rate:	Is faster than Butyl
Solubility in H2O.....	Negligible		Acetate
Freeze Point.....	N.D.	Specific Gravity:	0.6925
Vapor Pressure.....	N.D.	pH @ 0.0%	N.A.
Physical State	Liquid	Viscosity:	N.D.
Coefficient of Water/Oil Distribution:	N.D.		

(See Section 16 for abbreviation legend)

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Heat, sparks, welding arcs, open flame, pilot lights, static electricity or other source of ignition.

INCOMPATIBILITY: oxidizing agents, acids, reducing agents, strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS: carbon monoxide and carbon dioxide, various hydrocarbons, sulfur dioxide, sulfur monoxide.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

SECTION 11 - TOXICOLOGICAL PROPERTIES

No product or component toxicological information is available.

SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information.

SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

SECTION 14 - TRANSPORTATION INFORMATION

DOT Proper Shipping Name	Consumer Commodity	IATA UN/ID Number	ID8000
DOT Hazard Classification	ORM-D	IATA Class or Division	9
DOT Identification Number		IATA Proper Shipping Name	Consumer Commodity
		IATA Labels	Miscellaneous
IMDG	UN1950		
IMDG Class	2.1		
IMDG Proper Shipping Name	Aerosols		
IMDG Labels	Flammable Gas		

Additional Information: For domestic ground and air shipment this product may be shipped as a Consumer Commodity ORM-D. Outer cartons must have the ORM-D or ORM-D AIR designation. (our original cartons are preprinted with the ORM-D designation for ground shipment)

SECTION 15 - REGULATORY INFORMATION

U.S Federal Regulations: As Follows:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA – SARA, HAZARD CATEGORY: This product has been reviewed according to the EPA ‘Hazard Categories’ promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD - CHRONIC HEALTH HAZARD - FIRE HAZARD - PRESSURIZED GAS HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

CHEMICAL NAME:	CAS NUMBER	WT/WT% IS LESS THAN
Hexane	110-54-3	35.0%

TOXIC SUBSTANCES CONTROL ACT: This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States.

CHEMICAL NAME:	CAS NUMBER
-----------------------	-------------------

No information is available

INTERNATIONAL REGULATIONS: AS FOLLOWS:

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

Hexane is a mixture of n-hexane and other compounds all falling under the general chemical name light hydrotreated distillate CAS-68410-97-9. The n-hexane content of our hexane is 60 to 70 percent. On June 30 1993 the OSHA Z-1-A table was revoked and OSHA reverted back to their prior exposure limits. The values on this MSDS reflect the roll back to the prior values. Some states may continue to enforce the 1993 limits. On June 16 1995 EPA announced in a final rule that acetone would no longer be considered a VOC for air attainment standards. (it is now an exempt compound). The VOC Calculations on this MSDS are based on acetone being an exempt compound. The June 16 rule also removed acetone from the list of SARA 313 reportable chemicals.

SECTION 16 - OTHER INFORMATION

HMIS Ratings – Health: 2 Flammability: 4 Reactivity: 1

Previous MSDS revision Date: 02/11/03

Reason for Revision: New Low Voc Formula

VOC Content: 63.6% by weight, 439 Grams/Liter Total Product
512 Grams/Liter less water and exempt, 0.57 lbs/can

Legend: N.A. – Not Applicable

N.E. – Not Established

N.D. – Not Determined

DISCLAIMER

The information on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations. The environmental information and hazardous materials identification system have been included in order to provide additional health and hazard classification information. The ratings recommended are based upon the criteria supplied by the developers of these rating systems. Proper personal protective equipment varies widely with conditions of use and anticipated exposure. We recommend that a supervisor or other qualified person determine proper PPE for intended use.