



SAFETY DATA SHEET

High Performance Zinc Spray

Part No. None Aerosol

Revision 8

Page 1 of 8

SECTION 1 - IDENTIFICATION

Product Identifier

Product Number(s) None
Product Name High Performance Zinc Spray

Other Means of Identification None

Recommended Use and Restrictions on Use

Recommended Use Zinc rich protective coating.
Restrictions on Use None Identified

24 hr Emergency Phone Number
800-255-3924 (Chem-Tel)

MANUFACTURER DETAILS		SUPPLIER DETAILS	
Name	Clearco Products, Inc.	Name	Clearco Products, Inc.
Address	15 York Road Willow Grove, PA 19090	Address	15 York Road Willow Grove, PA 19090
Phone Number	215-366-7860	Phone Number	215-366-7860
Fax Number	215-366-7862	Fax Number	215-366-7862

SECTION 2 - IDENTIFICATION

Hazard Classification

HEALTH HAZARDS				PHYSICAL HAZARDS					
Acute Tox. Oral	<input type="checkbox"/>	Mutagenicity	<input type="checkbox"/>	Unstable Explosive	<input type="checkbox"/>	Refrigerated Liq. Gas	<input type="checkbox"/>	Pyrophoric Solid	<input type="checkbox"/>
Acute Tox. Skin	<input type="checkbox"/>	Carcinogenicity	<input type="checkbox"/>	Explosive	<input type="checkbox"/>	Flammable Liquid	<input type="checkbox"/>	Emits Flammable Gas	<input type="checkbox"/>
Acute Tox. Inhalation	<input type="checkbox"/>	Tox. to Reproduction	<input type="checkbox"/>	Flammable Gas	<input type="checkbox"/>	Flammable Solid	<input type="checkbox"/>	Oxidizing Liquid	<input type="checkbox"/>
Skin Irritation	<input type="checkbox"/>	STOT SE	3	Aerosol	1	Self-Reactive Sub.	<input type="checkbox"/>	Oxidizing Solid	<input type="checkbox"/>
Eye Irritation	2	STOT RE	<input type="checkbox"/>	Oxidizing Gas	<input type="checkbox"/>	Pyrophoric Liquid	<input type="checkbox"/>	Organic Peroxide	<input type="checkbox"/>
Resp. Sensitization	<input type="checkbox"/>	Aspiration Hazard	<input type="checkbox"/>	Gas Under Pressure	X	Self-Heating Substance	<input type="checkbox"/>	Corrosive to Metal	<input type="checkbox"/>
Skin Sensitization	1		<input type="checkbox"/>	ENVIRONMENTAL HAZARDS (GHS Rev 3 Only)					
	<input type="checkbox"/>		<input type="checkbox"/>	Aquatic Acute	1	Aquatic Chronic	1	Ozone Depleting	<input type="checkbox"/>

Signal Word

Danger

Hazard Pictograms



Hazard Statements

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May cause an allergic skin reaction. Causes serious eye irritation. May cause drowsiness or dizziness. Very toxic to aquatic life with long lasting effects.

Precautionary Statements

General

Keep out of reach of children.

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release into the environment.



SAFETY DATA SHEET

High Performance Zinc Spray

Part No. None Aerosol

April 10, 2019

Revision 8

Page 2 of 8

Response *IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Call a POISON CENTER or doctor if you feel unwell. Collect spillage.*

Storage *Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F.*

Disposal *Dispose of contents/container in accordance with local regulations.*

Hazards Not Otherwise Classified *None identified.*

Unknown Acute Toxicity *48 % by wt*

SECTION 3 - COMPOSITION / INFORMATION ON INGREDIENTS

1	Zinc	0007440-66-6	30 - 60
2	Liquefied Petroleum Gas	0068476-86-8	15 - 40
3	Methyl Ethyl Ketone	0000078-93-3	15 - 40
4	Stoddard Solvent	0008052-41-3	3 - 7
5	Xylene	0001330-20-7	0.5 - 1.5
6	Organophilic Clay	0071011-24-0	0.5 - 1.5
7	Ethyl Benzene	0000100-41-4	0.1 - 1

** Exact percentages of composition withheld as trade secret*

SECTION 4 - FIRST AID MEASURES

Description of First-Aid Measures

General *If exposed or concerned seek medical advice/attention.*

Eye Contact *Immediately flush with clear water for at least 15 minutes, including under the eyelids. Consult a doctor.*

Skin Contact *Remove with soap and water, rinsing and repeating for 15 minutes. Use skin cream to counter any resulting dryness. Consult a physician if irritation continues. If large skin area is affected, remove contaminated clothing.*

Ingestion *Do not induce vomiting! Immediately have the victim drink plenty of water. Do not give milk or digestible oils. Keep airways free. Contact a physician. Never give anything by mouth if victim is rapidly losing consciousness, unconscious, or convulsing.*

Inhalation *Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention if symptoms persist or if unconscious.*

First-Aid Responder Protection *Wear adequate personal protective equipment based on the nature and severity of the emergency.*

Most Important Symptoms and Effects, Both Acute and Delayed

Eye Contact *Liquid contact may cause pain along with moderate eye irritation.*

Skin Contact *Prolonged or repeated exposure may cause skin irritation. Repeated contact may cause drying or flaking of skin. May cause more severe response if confined to skin.*

Ingestion *Due to being an aerosol, the product does not lend itself to ingestion. Should ingestion occur, it may cause irritation to membranes of the mouth, throat, and gastrointestinal tract resulting in vomiting and/or cramps. Aspiration of vomit into the lungs may cause inflammation, and possible chemical pneumonitis, bronchopneumonia, or pulmonary edema.*

Inhalation *Prolonged or repeated overexposure is anesthetic. May cause irritation of the respiratory tract, or acute nervous system depression characterized by headache, dizziness, staggering gait, confusion or death. Irritation of the mucous membranes, coughing, and dyspnea are also possible.*

Indication of Immediate Medical Attention and Special Treatment

Notes to Physician *Stoddard Solvent sensitizes the heart to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmia in individuals exposed. Use of sympathomimetic drugs should be avoided. If ingested, the material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left later lateral decubitus position.*

Specific Treatments/Antidotes *No information available.*



SAFETY DATA SHEET

High Performance Zinc Spray

Part No. Non-Aerosol

April 10, 2019

Revision 8

Page 3 of 8

Immediate Medical Attention

No information available.

SECTION 5 - FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media *Water, CO2, dry chemical, or universal aqueous film forming foam*

Unsuitable Extinguishing Media *Water jet*

Specific Hazards Arising from the Chemical or Mixture

Decomposition Products *Oxides of carbon (CO, CO2), smoke, and/or vapors*

Hazards from the Product *CONTENTS EXTREMELY FLAMMABLE AND UNDER PRESSURE. In a fire or if heated, a pressure increase will occur which may result in the container bursting. Vapors heavier than air may spread along the ground and travel to an ignition source.*

Advice for Firefighters

Protective Actions *Use water spray to cool fire exposed containers as contents may rupture violently from heat developed pressure.*

Protective Equipment *As with any fire wear SCBA pressure-demand, MSHA/NIOSH approved, and full protective gear.*

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

For Non-Emergency Personnel *No action should be taken by non-emergency personnel without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spill. Remove sources of ignition and provide adequate ventilation only if it is safe to do so.*

For Emergency Responders *Use personal protection as recommended in Section 8. Observe precautions provided for non-emergency personnel.*

Environmental Precautions

Precautions *Keep out of drains, sewers, ditches, and waterways. Minimize use of water to prevent environmental contamination.*

Methods and Materials for Containment and Cleaning Up

Containment Procedures *Product is an aerosol, therefore spills and leaks are unlikely. In case of rupture, released content may be contained with oil/solvent absorbent pads, socks, and/or absorbents. DO NOT use combustible material such as sawdust.*

Cleanup Procedures *Spills from aerosol cans are unlikely and are generally of small volume. Large spills are therefore not normally considered a problem. In case of actual rupture, avoid breathing vapors and ventilate area well. Remove sources of ignition and use non-sparking equipment. Soak up material with inert absorbent and place in safety containers for proper disposal.*

Other Information *Aerosol products represent a limited hazard and will not spill or leak unless ruptured. In case of rupture contents are generally evacuated from the can rapidly. Area should be ventilated immediately and continuous ventilation provided until all fumes and vapors have been removed. Aerosol cans should never be incinerated or burned. See Section 13 for disposal.*

Prohibited Materials *Combustible absorbent material such as sawdust, use of equipment that may cause sparking.*

SECTION 7 - HANDLING AND STORAGE

Precautions for Safe Handling

General Handling Precautions *KEEP OUT OF THE REACH OF CHILDREN. Avoid prolonged or repeated skin contact. Avoid breathing of vapors. Do not incinerate (burn) containers. Always replace overcap when not in use. Avoid use around open flames or other sources of ignition. Exposure to heat or prolonged exposure to sun may cause can to burst. Use only with adequate ventilation, opening doors or windows to achieve cross-ventilation. Wash hands after use.*

Hygiene Recommendations *Do not eat, drink or smoke when using this product. Wash hands thoroughly after use. Remove contaminated clothing and protective equipment before entering eating or smoking areas.*



SAFETY DATA SHEET

High Performance Zinc Spray

Part No. Non-Aerosol

April 10, 2018

Revision 8

Page 4 of 8

Conditions for Safe Storage Including Any Incompatibilities

Storage Requirements *Storage of individual cans should be done in an area below 50 °C (122 °F), and away from heat sources. Ensure can is in a secure place to prevent knocking over and accidental rupture. For storage of pallet quantities, compliance with NFPA 30B (Manufacture and Storage of Aerosol Products) is recommended. This product is classified as a Level 3 Aerosol.*

Incompatibilities *Segregate storage away from materials indicated in Section 10*

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Control Parameters

Occupational Exposure Limits

ID	PEL	OSHA STEL	CEILING	IDLH	REL	NIC SH	STEL	CEILING	TLV	ACGIH STEL	CEILING	AIHA WEEL
2	1000 ppm	–	–	2000 ppm	1000 ppm	–	–	–	1000 ppm	–	–	–
3	200 ppm	–	–	3000 ppm	200 ppm	–	300 ppm	–	200 ppm	300 ppm	–	–
4	500 ppm	–	–	20000 mg/m ³	350 mg/m ³	–	–	1800 mg/m ³	100 ppm	–	–	–
5	100 ppm	–	–	900 ppm	100 ppm	–	150 ppm	–	100 ppm	150 ppm	–	–
7	100 ppm	–	–	800 ppm	100 ppm	–	125 ppm	–	20 ppm	–	–	–

Biological Exposure Indices

3	MEK in urine		End of shift	2 mg/L	–
5	Methylhippuric acids in urine		End of shift	1.5 g/g creatinine	–
7	Sum of mandelic acid and phenyl alcoxvlic acid in urine		End of shift at end of workweek	0.7 a/a creatinine	Ns. Sa

Other Control Parameters *Not Available*

Appropriate Engineering Control

Engineering Measures *Use only with adequate ventilation. General ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. Local exhaust ventilation or an enclosed handling system may be necessary to control air contamination below that of the lowest OEL from the table above.*

Individual Protection Measures

Hygiene Considerations *Avoid breathing vapors and contact with the skin and eyes. Always replace overcap when not in use. Keep out the reach of children. Wash hands after use.*

Thermal Protection *This product does not present a thermal hazard.*

Respiratory Protection *An approved respirator with organic vapor cartridge may be permissible under certain circumstances where airborne concentrations are expected to exceed occupational exposure limits. If respirators are needed, compliance with OSHA standard 29 CFR 1910.134 is necessary.*

Skin Protection *For brief contact, no precautions other than clean body-covering clothing should be needed. When prolonged or repeated contact could occur, use protective clothing impervious to the ingredients listed in Section 2.*

Eye/Face Protection *Safety glasses with side shields are recommended as a minimum for any type of industrial chemical handling. Where eye contact with this material could occur, chemical splash proof goggles are recommended.*

Other Protective Equipment *Safety showers and eye-wash stations should be available in the workplace near where the material will be used.*

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical Properties

Boiling Point	> 79.4 °C (175.0 °F)	Melting / Freezing Point	> -86.0 °C (-122.8 °F)
Flash Point, Liquid	> -9.0 °C (15.8 °F)	Flash Point, Propellant	-104.4 °C (-156.0 °F)
Explosive Limits	1.80% - 10.00%	Autoignition Temperature, Liquid	404.0 °C (759.2 °F)
Flammability	Extremely Flammable Aerosol	Relative Density (H2O = 1)	1.054 g/cc
Molecular Weight	Not Available	Weight	8.800 lbs/gal
Vapor Pressure	70.00 psig	pH	Not Available
Vapor Density	2.410 g/cc Maximum	Evaporation Rate	Not Available



SAFETY DATA SHEET

High Performance Zinc Spray

Part No. None Aerosol

April 10, 2019

Revision 8

Page 5 of 8

Form	<i>Pressurized Product</i>	Partition Coefficient	<i>Not Available</i>
Viscosity	<i>Not Available</i>	Refractive Index	<i>Not Available</i>
Odor Threshold	<i>Not Available</i>	Heat of Combustion (ΔHc)	<i>Not Available</i>
Odor	<i>Paint-like</i>	Water Solubility	<i>Not Available</i>
Appearance / Color	<i>Gray Color Coating</i>	Decomposition Temperature	<i>Not Available</i>

Air Quality Properties

Percent Volatile	<i>56% Wt (88% Vol) Max</i>	VOC Regulatory	<i>4.871 lbs/gal (583.617 g/L)</i>
Percent VOC	<i>56% Wt (88% Vol) Max</i>	VOC Actual	<i>4.871 lbs/gal (583.617 g/L)</i>
Percent HAP	<i>2% Wt (2% Vol) Max</i>	HAP Content	<i>0.123 lbs/gal (14.631 g/L)</i>
Solids/Non Volatile Content	<i>45% Wt (13% Vol) Max</i>	Maximum Incremental Reactivity	<i>0.851 g O3/g</i>
Global Warming Potential	<i>2.000</i>		

SECTION 10 - STABILITY AND REACTIVITY

Reactivity *No specific test data related to reactivity is available for this product or its ingredients.*

Chemical Stability *This product is stable.*

Hazardous Reactions *Under normal conditions of storage and use, hazardous reactions are not expected to occur.*

Conditions to Avoid *Keep away from heat, sparks, flame, and red hot metal.*

Material Incompatibility *Acids, Alkalis, Amines, Ammonia, Chlorine Dioxide, Dichlorohydrantion, Hydrogen Peroxide, Isocyanates, Nitric Acid, Potassium Tert-Butoxide, Pyridines, Strong Acids, Strong Oxidizing Agents, Strong Reducing Agents*

Decomposition Productions *Oxides of Carbon, Aldehydes, Hydrogen Peroxide may be formed depending on fire conditions.*

SECTION 11 - TOXICOLOGICAL INFORMATION

Acute Toxicity Estimates (mixture)

Oral LD₅₀	<i>3006 mg/kg</i>
Dermal LD₅₀	<i>5204 mg/kg</i>
Inhalation LC₅₀	<i>704 mg/L 4-hour</i>

Acute Toxicity on Ingredients

ID	ORAL LD50		DERMAL LD50		INHALATION LC50		
	VALUE	SPECIES	VALUE	SPECIES	VALUE	TIME	SPECIES
2	-	-	-	-	658 mg/L	4h	rat
3	2740 mg/kg	rat	>8050 mg/kg	rat	11300 ppm	4h	rat
4	>5000 mg/kg	rat	>3000 mg/kg	rabbit	>5500 mg/m3	4h	rat
5	4300 mg/kg	rat	4500 mg/kg	rabbit	6700 mg/L	4h	rat
7	4720 mg/kg	rat	15500 mg/kg	rabbit	4000 ppm	4h	rat

Health Hazard Classification

Skin Corrosion / Irritation	<i>Classification criteria not met</i>
Eye Damage / Irritation	<i>Category 2</i>
Respiratory Irritation	<i>Classification criteria not met</i>
Respiratory / Skin Sensitization	<i>Category 1</i>
Germ Cell Mutagenicity	<i>Classification criteria not met</i>
Reproductive Toxicity	<i>Classification criteria not met</i>
STOT - Single Exposure	<i>Category 3</i>
STOT - Repeated Exposure	<i>Classification criteria not met</i>
Aspiration Hazard	<i>Classification criteria not met</i>

Carcinogen Data

ID	Calif Prop-65	OSHA	NIOSH	ACGIH	NTP	IARC
7	Yes	-	-	A3	-	2B



SAFETY DATA SHEET

High Performance Zinc Spray

Part No. Non-Aerosol

Revision 8

Page 6 of 8

Information on the Likely Routes of Exposure

Routes of Exposure *Skin contact, skin absorption, eye contact, inhalation*

Information on Physical, Chemical and Toxicological Effects

Symptoms of Exposure *Abdominal Cramps, Asphyxia, Chemical Pneumonitis, Coma, Dermatitis, Dizziness, Drowsiness, Excitation, Skin Irritation, Staggering Gait, Throat Irritation, Vomiting*

Delayed and Immediate Effects and also Chronic Effects from Short and Long-Term Exposure

Delayed Effects *No known delayed effects.*

Immediate Effects *No known immediate effects.*

Chronic Effects *Reports have associated repeated and prolonged occupational overexposure to solvents with irreversible brain and nervous system damage (sometimes referred to as "Solvent or Painter's Syndrome"). Intentional misuse by concentrating and inhaling this product may be harmful or fatal. Stoddard Solvent when ingestion and subsequent aspiration into the lungs may cause pneumatocele (lung cavity) formation and chronic lung dysfunction. Chronic exposure to zinc may cause respiratory tract irritation with nasopharyngitis and laryngitis.*

Medical Conditions Aggravated *May aggravate personnel with pre-existing disorders associated with any of the Target Organs.*

Target Organs *Blood, Central Nervous System, Eyes, Gastrointestinal Tract, Kidneys, Liver, Respiratory System, Skin*

SECTION 12 - ECOLOGICAL INFORMATION

Acute Aquatic Toxicity

ID	TYPE	FISH			INVERTEBRATES			AQUATIC PLANTS			MICROORGANISMS		
		VALUE	PERIOD	TYPE	VALUE	PERIOD	TYPE	VALUE	PERIOD	TYPE	VALUE	PERIOD	
3	LC50	5600 mg/L	96h	EC50	5091 mg/L	48h	ICS	>4300 mg/L	7d	EC5	1150 mg/L	16h	
5	LC50	26.7 mg/L	96h	LC50	14 mg/L	24h	-	-	-	-	-	-	
7	LC50	97.1 mg/L	96h	LC50	77 mg/L	24h	EC50	63 mg/L	3h	EC50	130 mg/L	48h	

Ecological Data

ID	PERSISTENCE	PERSISTENCE AND DEGRADABILITY			BIOACCUMULATIVE POTENTIAL		MOBILITY
		BOD	COD	ThOD	Pow / Kow	BCF	
3	-	2030 mg/g	2310 mg/g	2440 mg/g	0.29 log Pow	1.34 log BCF	0.72 log Koc
4	-	-	-	-	3.16 log Pow	-	-
5	-	0.64 mg/L	-	2410 mg/g	3.271 log Pow	2.2557 log BCF	3.156 log Koc
7	-	1780 mg/g	-	3170 mg/g	3.15 log Pow	1.18 log BCF	2.4 log Koc

Other Adverse Effects *No additional information available.*

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal

Characteristics and waste stream classification can change with product use and location. It is the responsibility of the user to determine the proper storage, transportation, treatment, and/or disposal methodologies for spent materials and residues at the time of disposition. All waste must be disposed of in compliance with the respective national, federal, state, and/or local regulations.

Waste Disposal of Packaging

An aerosol container that does not contain a significant amount of liquid would meet the definition of scrap metal (40 CFR 261.1(c)(6)), and would be exempt from RCRA regulation under 40 CFR 261.6(a)(3)(iv) if it is to be recycled. If containers are to be disposed of (not recycled) it must be managed under all applicable RCRA and state regulations.

Landfill Precautions

Not available

Incineration Precautions

**** DO NOT INCINERATE ** CONTENTS UNDER PRESSURE ****



SAFETY DATA SHEET

High Performance Zinc Spray

Part No. None Aerosol

April 10, 2015
Revision 8

Page 7 of 8

SECTION 14 - TRANSPORTATION INFORMATION

Transportation Information

UN Number
Proper Shipping Name
Hazard Class(es)
Packaging Group
Marine Pollutant
Hazard Label(s)

Ground Transportation (DOT)

UN1950
Aerosols, Limited Quantity
2.1
—
No



Air Transportation (IATA)

UN1950
Aerosols, Flammable, Limited Quantity
2.1
—
No



Ocean Transportation (IMDG)

UN1950
Aerosols, Limited Quantity
2.1
—
No



NMFC Shipping Information (United States only) Paint Related Material
#149980 Sub 3, Class 60

SECTION 15 - REGULATORY INFORMATION

Federal Regulations

ID	TSCA LISTED	SARA 302 EHS TPQ	RCRA	CERCLA	SARA 313	FIRE	REACTIVITY	SARA 311/312 ACUTE	CHRONIC	PRESSURE	CLEAN HAP	ACT SOCMI	CLEAN WATER ACT
1	Yes	—	—	1000	38%	—	Yes	—	—	—	—	—	>1 (PP)
2	Yes	—	—	—	—	Yes	—	—	—	—	—	—	—
3	Yes	—	D035, U159	5000	—	Yes	—	Yes	—	—	—	—	—
4	Yes	—	—	—	—	—	—	Yes	—	—	—	—	—
5	Yes	—	U239	100	1%	Yes	—	Yes	—	—	Yes	Yes	100
6	Yes	—	—	—	—	—	—	—	—	—	—	—	—
7	Yes	—	—	1000	>1%	Yes	—	Yes	—	—	Yes	Yes	1000 (PP)

State Regulations

ID	CA P-65	DE RQ	MA RTK CODES	IL E TYPE	RQ	RTK	MN AIR	WATER	NJ RTK	AIR	NY LAND	ACUTE	PA LISTED	WA PEL TWA	WI TABLE	WV TAP
1	—	1000	5 F1 F8 F9	—	—	—	—	Yes	Yes	1000	100	—	Yes-*E	—	—	—
3	—	5000	2,4,5,6 F8 F9	—	2000	ANO	Yes	—	Yes	5000	1	—	Yes-E	—	—	—
4	—	—	2,4	—	—	ANO	—	—	—	—	—	—	Yes	100 ppm	A	—
5	—	100	2,4 F8 F9	—	2000	ANO	Yes	—	Yes	1000	1	—	Yes-E	100 ppm	A	—
7	C	1000	2,4,5,6 F7 F8 F9	—	2000	AO	Yes	Yes	Yes	1000	1	—	Yes-E	100 ppm	A	—

SECTION 16 - OTHER INFORMATION

SDS Revision History

Revision 3, 06/14/2004, General Update.
Revision 4, 11/08/2007, Total update to GHS format.
Revision 5, 02/17/2012, Date change
Revision 6, 11/15/2013, Updated to GHS Version 4 Format.
Revision 7, 07/07/2014, Added National Motor Freight Information (US only) to Section 14 at customer's request.
Revision 8, 04/16/2015, Amended to GHS Version 3 Format.

SDS Compliance

This SDS complies with the below listed regulations only. For SDS that comply with other countries, please contact our Regulatory Department at msds@chem-pak.com
OSHA Hazard Communication Standard (HCS 2012) 29 CFR 1910.1200
Globally Harmonized System of Classification and Labeling of Chemicals (GHS) Revision 3



SAFETY DATA SHEET

High Performance Zinc Spray

Part No. None Aerosol

April 10, 2019

Revision 8

Page 8 of 8

Disclaimer of Liability

The information contained herein is based upon data provided to us by our suppliers, and reflects our best judgement. However, no warranty of merchantability, fitness for any use, or any other warranty or guarantee is expressed or implied regarding the accuracy of such data, or the results to be obtained from use thereof. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, we do not assume any responsibility for the results of such application. This information is furnished upon the condition that the persons receiving it shall make their own determinations of the suitability of the material for any particular use. Although certain hazards are described herein, we cannot guarantee these are the only hazards that exist.